

EXPOSE TYPE ME132 D PROSCREEN 32"-DESKTOP-MONITOR

Features

- 32" industrial monitor
- 1,6 Ghz-Intel®-Atom™-Technology
- RAM 1GByte
- Resolution: 1.366x768 pixels
- Colors: 16.78 million
- Reading angle v/h: 178°
- Brightness: 450 cd/m²
- Contrast: 3.000 :1
- Integrated interfaces: 2x Ethernet, 2x USB, 1x RS232, 1x VGA-output,
- Mounting via variable adjustable ceiling and wall brackets (equipment)
- Protection class IP40
- Operating voltage: 100-240VAC



Advantages

- Trouble-free integration into existing networks
- Excellent readability from each side
- High resolution
- All connections accessible from the outside
- Temperature monitoring within case
- Cooling via dynamic fan-control
- Temperature-dependent backlight-off
- Robust, shapely industrial design
- Extensive equipment options
- Low power consumption: Eco-Design
- Quality "Made in Germany"

Options

- Screen sizes from 15" up to 55"
- Case finish in each RAL color
- Protection class up to IP65
- Ceiling and wall mounting with adjustable tilt angle

Applications

- Visualization of production data
- Meeting point
- Authority-information-system
- Factory-master-control-systems
- Logistic informations
- POS-systems

Technical data

Reading distance	Information on reading distance see www.WIBOND.de/service/d_leseentfernung.html
Display resolution	1.366 x 768 pixels
Reading angle vertical/horizontal	178°
Colors	16.78 Mio.
Number of pixels	about 1.049 Mio.
Operating voltage	100-240VAC / 50-60Hz / max. ,75 A
Power input (typ.)	75 W
Power input ("Backlight Off")	ca. 18 W
PC-components CPU	1,6 GHz Intel®-Atom™
PC-components RAM	1GByte
Operating system	
Ethernet interfaces	2x RJ45 / 1 GBit
USB interfaces	2x USB V2.0
Serielle interfaces	RS232
Case mounting	ceiling and wall mounting with adjustable tilt angle (optional equipment)
Case dimensions (width x height x depth)	744 x 434 x 80 mm
Temperature area	0 - 40 °C
Relative humidity	10 - 90 % not condensed
Weight	about 27 kg
Case material	sheet steel (powder coated)
Case color	on the front side: RAL9006 on the back side: RAL9005
Case protection classe IP40	DIN EN 60529
Electrical safety	DIN EN 60950-1
Radiated interference	DIN EN 61000-6-3
Interference immunity	DIN EN 61000-6-2
Filterpane	
Type	U1-10533-A