

AST3211-A1-D24

| | |
|---|--------------------------|
| Display Size (diagonal + wxh in mm) | 3.8 inch 76.7 x 57.5 |
| Display Type | Monochrome LCD |
| Display Colours | Amber 8 shades |
| Display Resolution | 320x240 pixels |
| Backlight | backlight LED |
| Touch Panel Type | Resistive Film (analog) |
| Touch Panel Resolution | 1024x1024 |
| Application Memory | 6 MB FEPROM |
| Data Backup Memory | 320 KB SRAM |
| Serial Interfaces | 2 |
| Com 1 | RS232 |
| com 2 | RS422/485 compatible MPI |
| Number of drivers that can be used simultaneously | 2 |
| PLC Control Functionality | No |
| CF-Card I/F | No |
| Ethernet I/F | No |
| USB I/F | Yes |
| Video input | No |
| Voltage | DC 24V |
| Ratings | IP65 |
| Operating Temperature | 0°C to 50°C |
| Housing | Plastic |
| External Dimensions (wxhxd in mm) | 130 X 104 X 40 |
| Cut-out Dimensions (wxh in mm) | 118.5 X 92.5 |
| Programming software | GP-Pro EX |



- ▶ AST3211-A1-D24
- ▶ Monochrome LCD
- ▶ Amber 8 shades
- ▶ 6 MB FEPROM

