

### GP2500-SC41-24V

Display Size (diagonal + wxh in mm)	10.4 inch 211.2 (W) x 158.4 (H)
Display Type	Colour STN
Display Colours	64 Colours
Display Resolution	640 x 480 pixels
Backlight	User replaceable CCFL
Touch Panel Type	Resistive Film (analog)
Touch Panel Resolution	1024x1024
Application Memory	4MB FLASH EPROM
Data Backup Memory	256KB
Serial Interfaces	1
Com 1	RS232/RS422/RS232C
Com 2	No
PLC Control Functionality	No
CF-Card I/F	Yes
Ethernet I/F	Yes
USB I/F	no
Video input	no
Voltage	DC24V
Ratings	IP65
Operating Temperature	0°C to 50°C
External Dimensions (wxhxd in mm)	317mm [12.48in.] x 243mm [9.57in.] x 58mm [2.28in.]
Cut-out Dimensions (wxh in mm)	301mm x 227.5mm
Programming software	GP-Pro PBIII



- ▣ GP2500-SC41-24V
- ▣ colour STN - 640 x 480
- ▣ 64 Colours
- ▣ RS232/RS422/RS232C - CF
- ▣ DC24V

### GP2600 Series / GP2500 Series

Photo shows GP-2600T

