

### AGP3500-L1-D24

Display Size (diagonal + wxh in mm)	10.4 inch (216.0 x 160.8)
Display Type	Monochrome LCD
Display Colours	16 shades of grey
Display Resolution	640x480 pixels
Backlight	CCFL service life 50000 hrs. at 25°C
Touch Panel Type	Resistive Film (analog)
Touch Panel Resolution	1024x1024
Application Memory	8 MB FEPROM
Data Backup Memory	320 KB SRAM
Serial Interfaces	2
Com 1	RS232/RS422/RS485
Com 2	RS422/RS485
Number of drivers that can be used simultaneously	4 (max)
PLC Control Functionality	No
CF-Card I/F	Yes
Ethernet I/F	Yes
USB I/F	Yes
Video input	No
Voltage	DC 24V
Ratings	IP65
Operating Temperature	0°C to 50°C
Housing	Aluminium
External Dimensions (wxhxd in mm)	313.0 X 239.0 X 56
Cut-out Dimensions (wxh in mm)	301.5 X 227.5
Programming software	GP-Pro EX



- ▣ AGP3500-L1-D24
- ▣ Monochrome LCD - 640 x 480
- ▣ 16 shades of grey
- ▣ RS232/RS422/RS485 - USB
- ▣ CF card
- ▣ DC 24V

