

AGP3500-L1-D24

| | |
|---|--------------------------------------|
| Display Size (diagonal + wxh in mm) | 10.4 inch (216.0 x 160.8) |
| Display Type | Monochrome LCD |
| Display Colours | 16 shades of grey |
| Display Resolution | 640x480 pixels |
| Backlight | CCFL service life 50000 hrs. at 25°C |
| Touch Panel Type | Resistive Film (analog) |
| Touch Panel Resolution | 1024x1024 |
| Application Memory | 8 MB FEPROM |
| Data Backup Memory | 320 KB SRAM |
| Serial Interfaces | 2 |
| Com 1 | RS232/RS422/RS485 |
| Com 2 | RS422/RS485 |
| Number of drivers that can be used simultaneously | 4 (max) |
| PLC Control Functionality | No |
| CF-Card I/F | Yes |
| Ethernet I/F | Yes |
| USB I/F | Yes |
| Video input | No |
| Voltage | DC 24V |
| Ratings | IP65 |
| Operating Temperature | 0°C to 50°C |
| Housing | Aluminium |
| External Dimensions (wxhxd in mm) | 313.0 X 239.0 X 56 |
| Cut-out Dimensions (wxh in mm) | 301.5 X 227.5 |
| Programming software | GP-Pro EX |



- ▣ AGP3500-L1-D24
- ▣ Monochrome LCD - 640 x 480
- ▣ 16 shades of grey
- ▣ RS232/RS422/RS485 - USB
- ▣ CF card
- ▣ DC 24V

