

LT3300-S1-D24-C

| | |
|-------------------------------------|---|
| Display Size (diagonal + wxh in mm) | 5.7 inch 117.2 x 88.4 |
| Display Type | STN Colour LCD |
| Display Colours | 4096 colours |
| Display Resolution | 320x240 pixels |
| Backlight | White LED |
| Touch Panel Type | Resistive Film (analog) |
| Touch Panel Resolution | 1024x1024 |
| Application Memory | 6 MB FEPROM |
| Data Backup Memory | 132 KB SRAM |
| Serial Interfaces | 1 |
| Com 1 | RS232C/RS422 |
| PLC Control Functionality | Yes - LADDER |
| CF-Card I/F | No |
| Ethernet I/F | Yes |
| USB I/F | Yes |
| Video input | No |
| Voltage | DC 24V |
| Ratings | IP65 |
| Operating Temperature | 0°C to 50°C |
| External Dimensions (wxhxd in mm) | 167.4 X 135 X 77.6 |
| Cut-out Dimensions (wxh in mm) | 156 X 123.5 |
| DIO | Input : Sink / source-type 16inputs output : Source-type 16outputs |
| Optional I/Os | EXM modules x 3 |
| Programming software | GP-Pro EX |



- ▣ LT3300-S1-D24-C
- ▣ STN Colour LCD - 320X240
- ▣ 4096 colours
- ▣ 16 inputs / 16 outputs - USB
- ▣ RS232C/RS422 - Ethernet
- ▣ DC 24V

