

ES-TB

Vandalism protected trackball

- *for public surroundings*
- *extrem weather conditions*
- *and many more*



ES-TB

stainless
steel

Description:

- A vandalism protected trackball in very robust processing.
- A full pointing device with the integrated 3 mouse buttons.
- Almost insensitive to violence.
- Mounting version with very low measurements for prepared mounting shafts.
- Explicitly for surroundings where there is danger by vandalism and/or much customer traffic and/or extrem weather conditions.
- Especially suitable for industrial extreme surroundings.

Order number for example:

notation: ES-TB AA PS2
article number: 02001AA251A1503EE00

More information to each variant and their order numbers, see our web-site at

www.dskeyboard.com

Features:

- All electronic components and mechanical guides are protected against ingress of dust and water spray (protection IP 65).
- Convenient and positive operation due to the 3,25 mm travel keys with tactile feel.
- Completely in stainless steel construction 1.4301 (buttons, front plate with 3 mm strength).
- Stainless steel bowl, 38mm, with protection IP 65 (static), IP 56 (dynamic).
- Key labelling in laser procedure.
- PCB with electronic components.
- Carbon contact-technology.
- Predestined for the work in public terminals, in machines and devices wich have to work in extreme damp (even splash water) or very dusty surroundings, and many more.

Mechanical Data:

- Travel 3,25 mm, tactile feel
- Operation force 0,65 N
- 3 buttons, 38mm stainless steel bowl
- Durability > 10 million ops.
- Storage temperature -40°C - +70°C
- Operation temperature 0°C - +60°C (optional -20°C - +60°C)
- Protection IP65

Layouts:

- All variants are possible.

Variants:

- Custom-designed variants are possible (see our web-site).

Connecting-Variants:

- PS/2, USB
- Cable straight or spiral-shaped
- Cable length 1,5 m
- Other length are possible

Detail views:

- Compact 15mm button arrangement, include 38mm stainless steel trackball.



Electrical Data:

- Power supply + 5 V/DC, 50 mA
- 2-key roll over
- Autorepeat
- 16k EEPROM memory
- CE-conformable
- EMC-conformable
- RoHS-conformable


Principle:

- Contact by a silicon switch pad with carbon contacts.


Use Possibilities:

- Extreme damp (even splash water) surroundings
- Very dusty surroundings
- Test- and measurement systems
- Machine- and device construction
- Trade and craft
- Industry
- Many frequented areas
- and any more

- Very robust steel construction
- Qualitatively excellent processing



Dimensions:



L1 = 94,00mm
L2 = 84,00mm
L3 = 76,00mm

B1 = 130,00mm
B2 = 120,00mm
B3 = 112,00mm

H = 24,00mm
H1 = 25,10mm
H2 = 3,00mm
H3 = 3,00mm
H4 = 40,50mm

More information about the measurements can be downloaded from our web-site.

ES-TB

stainless
steel

**DS Keyboard
Technic GmbH**

Herrenlandstr. 31-35
78315 Radolfzell

Tel.:
+49 (0) 7732-82385-0

Fax:
+49 (0) 7732-82385-29

Mail:
info@dskeyboard.com

Internet:
www.dskeyboard.com