

65T-ES-TB ATK

Vandalism protected keyboard

- *for public surroundings*
- *extrem weather conditions*
- *and many more*

65T-ES-TB ATK

stainless
steel



Description:

- A vandalism protected keyboard with 65 buttons in different layouts in robust processing.
- Integrated 38mm trackball with 3 mouse buttons
- Almost insensitive to violence.
- Mounting version for prepared mounting shafts.
- Explicitly for surroundings where there is danger by vandalism and/or much customer traffic and/or extrem weather conditions.
- Especially suitable for industrial extreme surroundings.

Order number for example:

notation: 65T-ES-TB ATK G

article number:

More information to each variant and their order numbers, see our web-site at

www.dskeyboard.com

Features:

- All electronic components and mechanical guides are protected against ingress of dust and water spray (protection IP 65).
- Convenient and positive operation due to the 1,5 mm travel keys with tactile feel.
- Completely in stainless steel construction 1.4301 (buttons, front plate with 1,5 mm strength).
- Stainless steel trackball with protection IP 65 (static), IP 56 (dynamic).
- Key labelling in laser procedure.
- PCB with electronic components.
- Carbon contact-technology.
- Predestined for the work in public terminals, in machines and devices wich have to work in extreme damp (even splash water) or very dusty surroundings, and many more.

Mechanical Data:

- Travel 1,5 mm, tactile feel
- Operation force 0,65 N
- 65 buttons, compact layout
- Durability > 1 million ops.
- Storage temperature -40°C - +70°C
- Operation temperature 0°C - +60°C (optional -20°C - +60°C)
- Protection IP65

Layouts:

- All variants are possible.

Variants:

- Custom-designed variants are possible (see our web-site).

Connecting-Variants:

- PS/2-PS/2 (keyb.-trackb.), USB
- Cable straight
- Cable length 1,5 m
- Other length are possible

Detail views:

- Ergonomic, compact quadratic 13x13 mm button arrangement include 38mm trackball.



Electrical Data:


- Power supply + 5 V/DC, max. 15 mA
- 2-key roll over
- Autorepeat
- CE-conformable
- EMC-conformable
- RoHS-conformable

Principle:



- Contact by a silicon switch pad with carbon contacts.

Use Possibilities:


- Extreme damp (even splash water) surroundings
 - Very dusty surroundings
 - Test- and measurement systems
 - Machine- and device construction
 - Trade and craft
 - Industry
 - Many freequented areas
 - and any more
-
- Robust steel construction
 - Very compact, flat style
 - Qualitatively excellent processing



Dimensions:



L1 =	380,00mm
B1 =	111,85mm
H1 =	42,70mm
H2 =	10,00mm
H3 =	1,50mm



More information about the measurements can be downloaded from our web-site.

65T-ES-TB ATK

stainless
steel

DS Keyboard Technic GmbH

Herrenlandstr. 31-35
78315 Radolfzell

Tel.:
+49 (0) 7732-82385-0

Fax:
+49 (0) 7732-82385-29

Mail:
info@dskeyboard.com

Internet:
www.dskeyboard.com