

### AGP3600-T1-D24-D81C

|   |   |
|---|---|
| Display Type                                      | Colour TFT  |
| Display Colours                                   | 65536 colours                                       |
| Display Resolution                                | 800x600 pixels                                      |
| Backlight   | CCFL service life 50000 hrs. at 25°C                |
| Touch Panel Type                                  | Resistive Film (analog)                             |
| Touch Panel Resolution                            | 1024x1024   |
| Application Memory                                | 8 MB FEPROM   |
| Data Backup Memory                                | 320 KB SRAM   |
| Serial Interfaces                                 | 2   |
| Com 1   | RS232/RS422/RS485                                   |
| Com 2   | RS422/RS485   |
| Number of drivers that can be used simultaneously | 4maxi   |
| PLC Control Functionality                         | Yes   |
| CF-Card I/F                                       | Yes   |
| Ethernet I/F                                      | Yes   |
| USB I/F   | Yes   |
| Video input                                       | No  |
| Voltage   | DC 24V  |
| Ratings   | IP65  |
| Operating Temperature                             | 0°C to 50°C   |
| Housing   | Aluminium   |
| External Dimensions (wxhxd in mm)                 | 313 X 239 X 56                                      |
| Cut-out Dimensions (wxh in mm)                    | 301.5 X 227.0                                       |
| DIO   | Sink/ Source type 6 inputs<br>Source type 2 outputs |
| CANopen Network                                   | No  |
| Flex Network                                      | No  |
| Programming software                              | GP- Pro EX  |



- ▣ AGP3600-T1-D24-D81C
- ▣ Colour TFT - 800 x 600
- ▣ 65536 colours
- ▣ RS232/RS422/RS485 - USB - Ether
- ▣ CF card - DIO 6 inputs/2 outputs
- ▣ DC 24V

