


AGP3500-T1-D24-CA1M

Display Size (diagonal + wxh in mm)	10.4 inch 216.0 x 160.8
Display Type	Colour TFT
Display Colours	65536 colours
Display Resolution	640x480 pixels
Backlight	CCFL service life 50000 hrs. at 25°C
Touch Panel Type	Resistive Film (analog)
Touch Panel Resolution	1024x1024
Application Memory	8 MB FEPROM
Data Backup Memory	320 KB SRAM
Serial Interfaces	2
Com 1	RS232/RS422/RS485
Com 2	RS422/RS485
Number of drivers that can be used simultaneously	4
PLC Control Functionality	Yes
CF-Card I/F	Yes
Ethernet I/F	Yes
USB I/F	Yes
Video input	No
Voltage	DC 24V
Ratings	IP65
Operating Temperature	0°C to 50°C
Housing	Aluminium
External Dimensions (wxhxd in mm)	270.5 X 212.5 X 57
Cut-out Dimensions (wxh in mm)	259.0 X 210.0
DIO	No
CANopen Network	512 bit I/O 128 integral I/O
Flex Network	No
Programming software	GP-Pro EX



- ▣ AGP3500-T1-D24-CA1M
- ▣ Colour TFT - 640 x 480
- ▣ 65536 colours
- ▣ RS232/RS422/RS485 - USB - Ether
- ▣ CF card - CANopen network
- ▣ DC 24V

